




Heyco® Straight-Thru Strain Relief Bushings

For Round Cables




WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	C	
UL Type Designation	AWG/ Conductors	Approximate Diameter		A		B		Maximum Panel Thickness ¹				Black	Body Length
		in.	mm.	Mounting Hole Dia. in.	mm.	To Prevent Rotation in.	mm.	in.	mm.		in.	mm.	
SJT	18/4	.360	9,1	.750	19,0								
	14/3	.370	9,4										
S & ST	18/2	.390	9,9	.750	19,0	.660	16,8	.062	1,6	1244	SR 7N-2	.750	19,1
	18/3	.405	10,3										
	16/2	.405	10,3										
	16/3	.430	10,9	.750-.781	19,0-19,8								
Same as SR 7N-2 above except								.125	3,2	1237	SR 7P-2	.750	19,1
SJ, SJT & SJO	16/2	.325	8,3	.875	22,2	.770	19,6	.125	3,2	1240	SR 7K-2	.750	19,1
	18/3	.330	8,4										
	14/2	.350	8,9										
	16/3	.355	9,0										
	18/4	.360	9,1										
Same as SR 7K-2 above except				See Schematic						1271	SR 7KR-2	.750	19,1
SJT	14/3	.370	9,4	.875	22,2	.770	19,6	.125	3,2	1247	SR 7W-2	.750	19,1
	12/3	.425	10,8										
S & ST	18/2	.390	9,9	.875	22,2	.770	19,6	.125	3,2	1250	SR 7L-2	.750	19,1
	18/3	.405	10,3										
	16/2	.405	10,3										
	16/3	.430	10,9										
Same as SR 7W-2 above except								.200	5,1	1250	SR 7L-2	.750	19,1
SJT	12/3	.425-.475	10,8-12,1	.875	22,2	.840	21,3	.125	3,2	1497	SR 31-2	.812	20,6
S & ST	14/2	.530	13,5	.875	22,2	.840	21,3	.062	1,6	1254	SR 8N-2	.828	21,0
	14/3	.560	14,2										
	12/2	.600	15,3										
Same as SR 8N-2 above except								.125	3,2	1260	SR 8P-2	.812	20,6
								.187	4,8	1274	SR 8L-1		
S	12/2	.600	15,2	1.093	27,7	1.000	25,4	.281	7,1	1287	SR 9P-2	1.00	25,4
	12/3	.635	16,1	1.125	28,6								
	10/2	.640	16,3	1.093	27,7								
S, ST & SO	10/3	.690	17,5	1.187	28,6								


Standard color black. Consult Heyco for white and other colors.
¹Maximum Panel Thickness-Part has additional clearance.



FOR SR-7KR-2 ONLY



STANDARD MOUNTING HOLES



- Sizes SR7 to SR9 for mounting hole diameters from .750" (19,0 mm) to 1.187" (28,6 mm).
- Protects the lifeline of your electric/electronic products by absorbing the forces of pull, push, and twist that may be exerted on the flexible power cord.
- Securely anchors, insulates, and protects cables at panel entry points.
- Standardize panel design! Fill unneeded SR mounting holes with Heyco Double "D" Plugs, page 3-23.
- Sizes for thin .062" (1,6 mm) panel available:
 SR 7N-2
 SR 8N-2
 See chart for details.
- See pages 3-24, 3-25 and 3-26 for SR hole punches and assembly tools.
- See page 3-13 for Quick Specs.